CXL 380-470C

Unity Gain, Broad-Band Base Station Antenna for 380 - 470 MHz

DESCRIPTION

- CXL 380-470C is a sturdy, 0 dBd, vertically polarized, omnidirectional base station antenna, which covers 380 - 470 MHz.
- The antenna is provided with our "C" mast bracket, which is a universal, epoxy-coated mounting bracket made of non-corrosive aluminium. The accompanying U-bolts and fittings are made of stainless steel.
- The antenna can be mounted on 27 to 65 mm dia. mast tubes and it is possible to lead the cable either along the inside or on the outside of the mast tube.
- The broad-banded antenna element is completely enclosed in a glass fibre shroud, which will ensure performance undisturbed by corrosive environments.
- To substantially reduce noise caused by atmospherical discharges, all metal parts in the antenna are DC-grounded. Consequently, the antenna shows a DC-short across the coaxial cable.
- This antenna is constructed to ensure long dependable service in all climates.



ORDERING DESIGNATIONS

TYPE	PRODUCT NO.
CXL 380-470C	100000509

SPECIFICATIONS


E. E. C. E. C. L.	
ELECTRICAL	
MODEL	CXL 380-470C
ANTENNA TYPE	$1/2$ λ , broad-banded
FREQUENCY	380 - 470 MHz
IMPEDANCE	Nom. 50 Ω
RADIATION	Omnidirectional
POLARIZATION	Vertical
GAIN	0 dBd
BANDWIDTH	90 MHz
SWR	≤ 2.0
MAX. POWER	150 W
ANTISTATIC PROTECTION	All metal parts DC-grounded (connector shows a DC-short)
MECHANICAL	
FILCHANICAL	
TEMP. RANGE	-30° C → +70° C
	-30° C → +70° C N-female
TEMP. RANGE	
TEMP. RANGE CONNECTOR	N-female
TEMP. RANGE CONNECTOR WIND SURFACE	N-female 0.042 m ² / 0.45 ft ²
TEMP. RANGE CONNECTOR WIND SURFACE WIND LOAD	N-female 0.042 m ² / 0.45 ft ² 49 N @ 160 km/h / 99.42 mph.
TEMP. RANGE CONNECTOR WIND SURFACE WIND LOAD MAX. WIND SPEED	N-female 0.042 m² / 0.45 ft² 49 N @ 160 km/h / 99.42 mph. 200 km/h / 125 mph.
TEMP. RANGE CONNECTOR WIND SURFACE WIND LOAD MAX. WIND SPEED COLOUR	N-female 0.042 m² / 0.45 ft² 49 N @ 160 km/h / 99.42 mph. 200 km/h / 125 mph. Marine white Radome: Polyurethane-coated glass fibre Mounting bracket: Seawater resistant aluminium,
TEMP. RANGE CONNECTOR WIND SURFACE WIND LOAD MAX. WIND SPEED COLOUR MATERIALS	N-female 0.042 m² / 0.45 ft² 49 N @ 160 km/h / 99.42 mph. 200 km/h / 125 mph. Marine white Radome: Polyurethane-coated glass fibre Mounting bracket: Seawater resistant aluminium, epoxy-coated
TEMP. RANGE CONNECTOR WIND SURFACE WIND LOAD MAX. WIND SPEED COLOUR MATERIALS TOTAL HEIGHT	N-female 0.042 m² / 0.45 ft² 49 N @ 160 km/h / 99.42 mph. 200 km/h / 125 mph. Marine white Radome: Polyurethane-coated glass fibre Mounting bracket: Seawater resistant aluminium, epoxy-coated Approx. 1.20 m / 47.25 in.




TYPICAL GAIN AND SWR CURVES

SWR Tr/IS11 SWR 0.5/Div CAL 5.50 4.50 4.50 3.50 2.50 1.00 350.000 MHz 15,0000 MHz/Div 500.000 MHz


TYPICAL RADIATION PATTERN (E-PLANE)




TYPICAL RADIATION PATTERN (H-PLANE)



MULTI-PURPOSE MOUNTING BRACKET







 $\ensuremath{\mathsf{PROCOM}}$ A/S reserve the right to amend specifications without prior notice.

02/06/15

